



ELECTRIC BAR TACKING
SEWING MACHINE

电脑打结机

由于采用了电脑直接驱动方式，启动/停车反应迅速。与传统机型相比机器时间缩短了约27%，使生产效率得到了进一步提高。

转速为3,200rpm
完全按照缝制数据进行高质量缝纫
通过操作盘即可设定抬压脚高度
耗电少
低噪音、低震动

Adopt computer direct drive ,which start or stop is very fast, which response time shorted about 27% compare with normal traditional machines,increase the production effect.

Sewing speed : 3200/RPM.
Exactly same high quality sewing as the data.
Setting the stepper height by control panel.
Save power.
Low noise and shock.

CC-430D-01S/02S

缝制范围：40x30mm

缝制物定位容易、正确抬压脚装置由脉冲马达驱动，抬压脚高度设定为2阶段。缝制物定位容易，大大缩短了设定时间。此外，可适当轻轻操作踏板，踏板回踏时反应极佳。降压脚噪音也得到大幅度降低，可轻松的进行作业。

Easy to fix the sewing fabric position , the presser has been driven by pulse motor, the height of presser has been set by 2 steps. It shorted setting time, which you can operate the stepper slightly, it's response is very fast, it has been down the noise and shock, easy to operate.



规格 Specification

型号 / Model	CC-430D
线迹样式 / Stitch Pattern	单针平缝 / single-needle flat seam
最高缝纫速度 / Maximum Sewing Speed	3200rpm
缝制区域(x-y) / Sewing Area (x-y)	最大40×30 mm / Maximum 40×30mm
送布方式 / Fabric Feeding Method	Y-\$间歇送布 (脉冲马达驱动方式) / Y-\$interval fabric feeding (impulse motor driven mode)
针距 / Needle Pitch	0.05 ~ 12.7 mm
针数 / Gauge	任意 (关于输入完成的图案缝纫, 参照“程序一览”) Random (about the sewing of the pattern after finishing the input, refer to “Summary of Programs”)
最大针数 / Maximum Gauge	210,000针 (包括增加针数200,000针) / 210,000 needles (including increased 200,000 needles)
抬压脚方式 / Presser Lifter Mode	脉冲马达驱动方式 / Impulse motor driven mode
压脚上升量 / Presser Lifting Amount 纽扣夹上升量 / Button Grip Lifting Amount	最大17mm / Maximum 17mm
使用旋梭 / Rotating Shuttle	半回转标准旋梭 (2倍旋梭另售) Semi-rotary standard rotating shuttle (double rotating shuttle is sold separately)
扫线装置 / Thread Sweeping Device	标准装备 / Standard device
切线装置 / Thread Cutting Device	标准装备 / Standard device
夹线装置 / Thread Clamping Device	标准装备 / Standard device
数据存储方式 / Data Storage Mode	闪存 (使用CF卡可增加任意缝纫图案) Flash memory (with CF card, it can increase any sewing pattern as will)
用户程序数 / Number Of User's Programs	50
循环程序数 / Number Of Cycle Programs	9个循环 (各15个程序) / 9 cycles (15 programs for each)
存储数据数 / Number Of Stored Data	已输入89种缝纫图案 / It has already input 89 kinds of sewing patterns (最多可以增加缝制数据200种。增加总针数约在200,000针以内 (It can add 200 kinds of sewing data at the most. Increased total gauge is within 200,000 needles)
马达 / Motor	AC伺服马达550W / AC servo motor 550W
重量 / Weight	机头: 约 56kg、操作盘: 约 0.6kg / Machine head: about 56kg, operation panel: about 0.6kg 控制箱: 14.2 ~ 16.2kg (因提供地区而异) / Control box: 14.2 ~ 16.2kg (vary from region to region)
电源 / Power	单相100V/220V / Single-phase 100V/220V 三相200V/220V/380V/400V 400VA / Three-phase 200V/220V/380V/400V 400VA
净重/N.W	150
毛重/G.W	200
包装尺寸/Measurement	1250*850*1350
体积/CBM	1.44m³